



PIN OUTS	
A	B
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9
NC	10

TEST CONDITION: LOW-VOLTAGE 15V INSULATION: UPON 1M ohm ELECTRIC CONDUCTION:INSIDE 1.5K ohm			
6	BRACKET:(D-SUB 9P) L- COMMON TYPE	1PCS	
5	HEX SCREWS:4-40UNC 4.8*11.8*2.75mm	2PCS	
4	DKN:(D-SUB 9P 09*09*) BLACK WITH NUT	1PCS	
3	CONNECTOR:DB9M BLACK SOLDER TYPE PIN:G/F, INSULATOR COLOR:BLUE	1PCS	
2	CONNECTOR:PITCH 2.54*2.54mm IDC 10P SOCKET (HAVE THREE/NO SR),BLACK	1PCS	
1	CABLE:UL2651 28AWG 9C FLAT CABLE GRAY PITCH:1.27mm 307mm	1PCS	
ITEM NO	DESCRIPTION	Q'TY	REMARK

PCCABLES.COM INC.	PRODUCT	DB9M to IDC 10pin cable	CUSTOMER	PCC	DRAWN	z. q. h	 THREE ANGLE PROJECTION
	CUS, NO	PCC07120	VERSION	1	CHECKED		
	DR, NO		DRAWN DATE	2009. 03. 05	APPROVERD		